

How to restore Nora floors using Diamond by Gorilla Pads

Purpose

To restore a Nora floor after initial installation or heavy traffic

Supplies and Equipment

Mop bucket and wringer

Wet mop and handle

Wet floor signs

Dust mop, frame, handle and dust pan

Swing machine or auto scrubber

Wet vacuum

Electric or battery burnisher

800 grit, 1500 grit and 3000 grit Diamond by Gorilla in the appropriate sizes

Neutral cleaner

Fresh water

Procedure

1. Prepare to restore floor.
 - a. Dust mop area to be restored and pick up any debris
 - b. Place wet floor signs around the area you are restoring
 - c. Fill fresh water in the mop bucket
 - d. Put proper dilution of neutral cleaner in the mop bucket
 - e. Place an 800 grit DBG pad on the swing machine or auto scrubber

2. Dip the wet mop into the bucket of neutral cleaner and saturate the floor with the solution.
3. Slowly and deliberately make 8 -10 passes over the area with the swing machine or auto scrubber (if using an auto scrubber do not vacuum up the solution during this step).
4. Using either the wet vacuum or the auto scrubber to vacuum the solution up.
5. Take the 800 DBG off the machine and replace with a 1500 grit DBG pad.
6. Repeat the procedure using the 1500 Grit DBG pad.
7. Take the 1500 grit DBG pad off the machine and replace it with the 3000 grit DBG pad.
8. Repeat the procedure using the 3000 grit DBG pad.
9. Place the 3000 grit DBG pad under the electric or battery burnisher and burish the area you have scrubber until the desirable gloss is obtained.

Accomplishment

By performing this procedure as needed, your Nora floor will be clean, attractive and easy to maintain.